

## SCX400クローラークレーンジブ定格総荷重表

単位 : t

ジブ長さ (m)	10	13	16	19	22	25	28	31
作業半径 (m)	10	13	16	19	22	25	28	31
3.5	40.00							
3.7	40.00	40.00						
4.0	35.45	35.40	4.2mx32.65t					
4.5	29.45	29.35	29.30	4.7mx27.35t				
5.0	25.15	25.05	25.00	24.95	5.3mx22.85t			
5.5	21.90	21.80	21.75	21.70	21.65	5.8mx20.00t		
6.0	19.40	19.30	19.20	19.15	19.10	19.05	6.4mx17.35t	6.9mx15.55t
7.0	15.70	15.65	15.55	15.50	15.45	15.35	15.30	15.25
8.0	13.20	13.10	13.00	12.95	12.90	12.80	12.75	12.65
9.0	11.35	11.25	11.10	11.05	11.00	10.95	10.85	10.80
10.0	9.7mx10.30t	9.80	9.70	9.65	9.55	9.50	9.45	9.35
12.0		7.80	7.65	7.60	7.55	7.45	7.40	7.30
14.0		12.3mx7.55t	6.30	6.20	6.15	6.05	6.00	5.90
16.0			14.9mx5.80t	5.25	5.15	5.05	5.00	4.90
18.0				17.5mx4.65t	4.40	4.30	4.20	4.15
20.0					3.80	3.70	3.65	3.55
22.0					20.1mx3.80t	3.25	3.15	3.05
24.0						22.7mx3.10t	2.75	2.70
26.0							25.3mx2.55t	2.35
28.0								27.9mx2.10t
ロープ掛本数	6	6	6	5	4	4	3	3